

# ATTENTION UTILITY CONTRACTORS

*United Fiberglass  
Of America, Inc.*

UL Listed Fiberglass Conduit Systems  
Conduit Hanger Supports and Accessories  
Conduit System Design  
Cable Pulling Accessories  
Fiberglass Boxes, Manholes and Enclosures



## **BELOW GROUND FIBERGLASS CONDUIT**

### **FEATURES:**

\*A 20' length of 4" fiberglass weighs only 16lbs. That's 84% less weight than rigid steel and 55% less weight than PVC! **Result—increased worker productivity.**

\*Due to its high strength and rigidity, direct burial is an alternative to concrete encasement. **Result—lower installed cost.**

\*Bell and spigot push-fit gasket joint requires no threading or adhesives. **Result—faster installation times.**

\*Corrosion resistant. Fiberglass conduit contains UV inhibitors, and is resistant to a wide variety of chemicals including road salts, jet fuels and acids. **Result—long system life.**

\*Thermal stability. Fiberglass conduit has an operating temperature range of  $-40^{\circ}$  to  $230^{\circ}$ F. **Result—fiberglass can be installed year round, and in a variety of harsh environments.**

\* Low co-efficient of friction. Fiberglass conduit dissipates heat much quicker than thermoplastic PVC and rigid steel and will not burn through. **Result—longer pulls with no conduit or cable damage.**

**UNITED  
FIBERGLASS**  
of America, Inc.

## **CALL US**

Let United Fiberglass assist you with  
your next duct bank project:

**SALES: (800) 905-7506**

**SALES@UNITEDFIBERGLASS.COM**

**OR CONTACT YOUR LOCAL SALES**

**REPRESENTATIVE**

**UNITED FIBERGLASS PRODUCTS ARE PROUDLY  
MANUFACTURED IN THE U.S.A**